

Building Mount
10-1/2" or 14" Dia.
Corridor
Walkways
Accent
Building Entrances



BL-25/30



BL-26/31



BL-27/32



BL-28/33

Specifications



Certifications The fixture shall be ETL and CETL listed for wet location. Also meets IP65 standard.

Ballast Housing Cast aluminum with a minimum thickness of 1/8". Mounting plate welded to ballast housing for J-box mounting. Conduit mounting available, consult factory. Housing is fully gasketed with 3/16" extruded EDPM cord gasket.

Lens Frame Cast aluminum mounted to ballast housing with 10-24 stainless steel Allen cap screws.

Lens Opal UV-stabilized polycarbonate (OP) is standard. Lens supplied with one-piece extruded silicone gasket.

Ballast Fluorescent ballast for CFT lamps are electronic (minus 20° C). Other fluorescent 13- through 18-watt quad tube is core & coil (0° C).

Finish BK-BZ-WH-GR-GY-NA thermoset polyester powder coat which is electrostatically applied and bonded by heat fusion thermosetting. CC available upon request.

BL

PROJECT
FIXTURE TYPE
CATALOG#

BL-25/26/27/28 30/31/32/33

 Some luminaires use fluorescent or high intensity discharge (HID) lamps that contain small amounts of mercury. Such lamps are labeled "Contains Mercury" and/or with the symbol "Hg." Lamps that contain mercury must be disposed of in accordance with local requirements. Information regarding lamp recycling and disposal can be found at www.lamprecycle.org

Product Order Guide

Series	Max Watts	Lamp Type	Voltage ¹	Finish ¹	Options
BL-25/26/27/28	26 CFT	CFT ²	120	BK Black	EMG ⁴ Emergency Battery Backup
	(2) 26 CFT	CFT ²	208	BZ Bronze	
	32 CFT	CFT ²	240	WH White	
	42 CFT	CFT ²	277	GR Green	
	13 CFQ	CFQ ²		NA Natural Aluminum	
	(2) 13 CFQ	CFQ ²		GY Gray	
	18 CFQ	CFQ ²		CC Custom Color	
	(2) 18 CFQ	CFQ ²			
	21 Watt 2-D	F212D			
	50 MH	E17			
	70 MH	E17			
	50 HPS ³	E17			
	70 HPS ³	E17			
	BL-30/31/32/33	26 CFT	CFT ²		
(2) 26 CFT		CFT ²			
32 CFT		CFT ²			
(2) 32 CFT		CFT ²			
42 CFT		CFT ²			
(2) 42 CFT		CFT ²			
38 Watt 2-D		F382D			
50 MH		E17			
70 MH		E17			
100 MH		E17			
50 HPS		E17			
70 HPS		E17			
100 HPS		E17			

1 Consult factory for other colors and voltages

2 CFQ = double biax, CFT = triple biax

3 70 HPS 120V only

4 BL-25/26/27/28 require remote EMG

Luminaire Dimensions

Luminaire	A		B		Weight	
	Inch	mm	Inch	mm	lbs.	kg
BL-25	10.50	267	7.90	201	12	5.4
BL-26	10.50	267	8.50	216	12	5.4
BL-27	10.50	267	8.50	216	12	5.4
BL-28	10.50	267	8.40	213	12	5.4
BL-30	14.00	356	7.90	201	16	7.3
BL-31	14.00	356	10.50	267	16	7.3
BL-32	14.00	356	10.50	267	16	7.3
BL-33	14.00	356	10.40	264	16	7.3

