

Building Mount
10-1/2" or 14" Dia.
Corridor
Walkways
Accent
Building Entrances



Specifications



Certifications The fixture shall be ETL and CETL listed for wet location.

Ballast Housing Cast aluminum with a minimum thickness of 1/8". Mounting plate welded to ballast housing for J-box mounting. Housing is fully gasketed with 3/16" extruded EDPM cord gasket.

Lens Frame Cast aluminum mounted to ballast housing with 8-32 or 10-24 stainless steel flat head screws.

Lens Opal UV-stabilized polycarbonate (OP) is standard. Lens supplied with a one-piece extruded silicone gasket.

Ballast Fluorescent ballasts for CFT and lamps are electronic (minus 20° C). Other fluorescent 13- through 26-watt quad tube is core & coil (0° C).

Finish BK-BZ-WH-GR-GY-NA thermoset polyester powder coat which is electrostatically applied and bonded by heat fusion thermosetting. CC available upon request.

PROJECT
FIXTURE TYPE
CATALOG#

BL-36/37/38/39

 Some luminaires use fluorescent or high intensity discharge (HID) lamps that contain small amounts of mercury. Such lamps are labeled "Contains Mercury" and/or with the symbol "Hg." Lamps that contain mercury must be disposed of in accordance with local requirements. Information regarding lamp recycling and disposal can be found at www.lamprecycle.org

Product Order Guide

Series	Max Watts	Lamp Type	Voltage ¹	Finish ¹	Options
BL-36/37	13 CFQ	CFQ ²	120	BK Black	EMG ³ Emergency Battery Backup
	(2) 13 CFQ	CFQ ²	208	BZ Bronze	
	18 CFQ	CFQ ²	240	WH White	
	(2) 18 CFQ	CFQ ²	277	GR Green	
	26 CFT	CFT ²		NA Natural Aluminum	
	(2) 26 CFT	CFT ²		GY Gray	
	32 CFT	CFT ²		CC Custom Color	
	42 CFT	CFT ²			
	50 MH	E17			
	70 MH	E17			
BL-38/39	50HPS	E17			
	70HPS	E17			
	26 CFT	CFT ²			
	(2) 26 CFT	CFT ²			
	32 CFT	CFT ²			
	(2) 32 CFT	CFT ²			
	42 CFT	CFT ²			
	(2) 42 CFT	CFT ²			
	50 MH	E17			
	70 MH	E17			
100 MH	E17				
50 HPS	E17				
70 HPS	E17				
100 HPS	E17				

1 Consult factory for other colors and voltages

2 CFQ = double biax, CFT = triple biax

3 BL-36 and BL-37 require remote EMG. 750 lumens output for 30 minutes, -20F start temperature. 10' remote distance lamp to backup.

Example: BL-36-70MH-E17-277-WH

Luminaire Dimensions

Luminaire	A		B		Weight	
	Inch	mm	Inch	mm	lbs.	kg
BL-36	10.50	267	7.00	178	11	5.0
BL-37	10.50	267	6.50	165	11	5.0
BL-38	14.00	356	7.50	190	15	6.8
BL-39	14.00	356	7.00	178	15	6.8

