

Building Mount
Corridor
Walkways
Accent
Building Entrances



BL-44



BL-45



BL-47



BL-48



BL-49

Specifications



Certifications

The fixture shall be ETL and CETL listed for wet location. Also meets IP65 standard.

Ballast Housing

Cast aluminum with a minimum thickness of 1/8". Mounting plate welded to ballast housing for J-box mounting. Conduit mounting available, consult factory. Housing is fully gasketed with 3/16" extruded EDPM cord gasket.

Lens Frame

Cast aluminum mounted to ballast housing with 10-24 stainless steel Allen cap screws.

Lens

Opal UV-stabilized polycarbonate (OP) is standard. Lens supplied with one-piece extruded silicone gasket.

Ballast

Fluorescent ballast for CFT lamp is electronic (minus 20° C). Other fluorescent 13- through 18-watt quad tube is core & coil (0° C).


Finish

BK-BZ-WH-GR-GY-NA thermoset polyester powder coat which is electrostatically applied and bonded by heat fusion thermosetting. CC available upon request.

BL

PROJECT
FIXTURE TYPE
CATALOG#

BL-44/45/47 48/49

 Some luminaires use fluorescent or high intensity discharge (HID) lamps that contain small amounts of mercury. Such lamps are labeled "Contains Mercury" and/or with the symbol "Hg." Lamps that contain mercury must be disposed of in accordance with local requirements. Information regarding lamp recycling and disposal can be found at www.lamprecycle.org

Product Order Guide

Series	Max Watts	Lamp Type	Voltage ¹	Finish ¹	Options
BL-44/45/47/48/49	26 CFT	CFT ²	120	BK Black	EMG Emergency Battery Backup
	(2) 26 CFT	CFT ²	208	BZ Bronze	
	32 CFT	CFT ²	240	WH White	
	42 CFT	CFT ²	277	GR Green	
	(2) 13 CFQ	CFQ ²		NA Natural Aluminum	
	(2) 18 CFQ	CFQ ²		GY Gray	
				CC Custom Color	
	50 MH	E17			
	70 MH	E17			
	50 HPS	E17			
70 HPS	E17				

¹ Consult factory for other colors and voltages

² CF = single biax, CFQ = double biax, CFT = triple biax

Note: EMG 750 lumens output for 30 minutes, -20F start temperature. 10' remote distance lamp to backup.

Example: BL-48-70MH-E17-277-WH

Luminaire Dimensions

Luminaire	A		B		C		Weight	
	Inch	mm	Inch	mm	Inch	mm	lbs.	kg
BL-44	14.00	356	8.00	203	7.50	191	9	4.1
BL-45	14.00	356	8.00	203	7.50	191	11	4.9
BL-47	14.00	356	8.00	203	7.50	191	12	5.4
BL-48	14.00	356	8.00	203	7.50	191	9	4.1
BL-49	14.00	356	8.00	203	7.50	191	11	4.9

