

Specification Grade

Sign Accent

Building Entrances

Doorways

Pedestrian Areas

Landscape Areas

Building Accent

Wall Wash



Specifications



Certifications ETL and CETL listed for wet location and meets IP65 standard, dust-tight and water-jet proof.

Fixture Housing/Knuckle The housing and knuckle is constructed of heavy wall die cast aluminum castings with a minimum 1/8" thickness.

Lens Clear tempered 3/16" thick, high temperature silicone gasket sealed to fixture housing.

Lens Frame Die cast aluminum minimum thickness of 1/8", attached to fixture housing with one center pinned latch and four rear mounted stainless steel cap screws.

Reflectors Spun aluminum highly specular Alzak™ finish for either type R2 spot (1H1V), R3 flood (3H3V) or R4 flood (4H4V) distributions. One segmented asymmetric reflector is available, type R5 (distribution varies with lamp).

Lamp Holder Porcelain 4kv pulse rated medium base for HID lamp sources.

Options Color Filter (CF), Polycarbonate Lens Shield (PL), Barndoors (BD), Grid Louver (GL), Long Visor (LV), Short Visor (SV), Full Visor (FV), Fusing (F), Double Fusing (FF), Photo Control Button (PCB). The Vertical Orientation (VO) allows the FL-02 to be configured in the vertical position. Note: when in the VO orientation the asymmetric optics are rotated 90°.

Mounting Detail The FL-02 Knuckle is field adjustable up to 136° tilt and 360° horizontal rotation and slips over a 2-3/8" tenon. The FL-02-K or FL-02-VO may be horizontal surface mounted using either the Pier Mount (PM) or Stanchion Mount (SM) options. The FL-02-K or FL-02-VO may be wall mounted using the Designer Wall Bracket (DWB), or Standard Wall Bracket (WBT). The FL-02-Y is field adjustable up to 300° tilt and 90° horizontal rotation and can be secured to any surface with two screws using a cast adaptor. Mounting hardware and junction box by others. Call factory for custom mounting arrangements.

Finish BK-BZ-WH-GR-GY-NA thermoset polyester powder coat which is electrostatically applied and bonded by heat fusion thermosetting. CC available upon request.

PROJECT
FIXTURE TYPE
CATALOG#

 Some luminaires use fluorescent or high intensity discharge (HID) lamps that contain small amounts of mercury. Such lamps are labeled "Contains Mercury" and/or with the symbol "Hg." Lamps that contain mercury must be disposed of in accordance with local requirements. Information regarding lamp recycling and disposal can be found at www.lamprecycle.org

Product Order Guide

Series	Mounting Type	Max Watts	Lamp Type	Voltage ¹	Reflector Type	Finish ²	Options	
FL-02	K Knuckle	26 CFT	CFT	120	R2 1H1V Spot	BK Black	PCB Photo Control Button	
	Y Yoke	32 CFT	CFT	208	R3 3H3V Flood	BZ Bronze	PL Polycarbonate Lens Shield	
	VO Vertical Orientation	60 PLH	PLH	E17	240	R4 ³ 7H7V Flood	WH White	BD Barn Doors
								GL Grid Louver
								LV Long Visor
								SV Short Visor
								FV Full Visor
								DWB Designer Wall Bracket
								PM Pier Mount
								SM Stanchion Mount
LED	Titan 25TC	CUS3 ⁴	25,45	120-277	TruColor (3050°K)	1290 Raw Lumens	F Fusing	
	Titan 25WW	CUS3 ⁴	25,45	120-277	Warm White (3050°K)		FF Double Fusing	
	Titan 25CW	CUS3 ⁴	25,45	120-277	Cool (Daylight) White (4700°K)			

¹ Consult factory for other voltages.

² Consult factory for other finishes. Powder coat paint standard.

³ Compact fluorescent limited to R4 and R5 reflector types. R4 only compact fluorescent.

⁴ The CUS3 uses a 25W Titan from Lamina with no tilt

Note: E17 Lamps 150W and below are medium base
CFT=triple biax, PLH=High

Example: FL-02-K-70MH-E17-277-R3-BK-DWB

FL-02 EPA 0.81 or 0.61 at 45° Tilt

Luminaire Dimensions

Luminaire	A		B		C		D		E		F		G		Weight	
	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	lbs.	kg
FL-02-K	7.00	178	11.88	302	10.00	254	6.59	167	11.19	284	11.73	298	n/a	n/a	25	11.3
FL-02-Y	11.16	283	11.88	302	12.52	318	6.59	167	9.18	233	7.00	178	n/a	n/a	20	9.1
PM	6.00	152	4.00	102	6.00	152	6.00	152	n/a	n/a	n/a	n/a	n/a	n/a	3	1.4
SM	2.375	60	24.00	610	4.09	104	3.00	76	n/a	n/a	n/a	n/a	n/a	n/a	4	1.8
WBT	10.00	254	2.375	60	3.00	76	8.00	203	12.00	305	4.00	102	6.00	152	7	3.2
DWB	4.31	109	7.50	191	9.50	241	8.00	203	n/a	n/a	n/a	n/a	n/a	n/a	5	2.3

